

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS

1. (Original) A method for on-demand management of Internet Protocol (IP) address pools, the method comprising:

allocating an unused IP address from a local IP address pool designated for a remote domain if a request to connect to said remote domain is received, said local IP address pool comprising one or more of at least one subnet obtained from a global IP address pool, each of said at least one subnet specifying a contiguous set of one or more IP addresses;

deallocating an IP address back to said local IP address pool if said IP address is unused; and

apportioning one or more of said at least one subnet between said global IP address pool and said local IP address pool based upon utilization of said local IP address pool.
2. (Original) The method of claim 1, further comprising configuring said local IP address pool with a subnet from said at least one subnet.
3. (Original) The method of claim 1 wherein said apportioning comprises:

requesting one or more subnet from said global IP address pool if utilization of said

local IP address pool exceeds a first threshold; and
releasing one or more subnet to said global IP address pool if utilization of said local
IP address pool falls below a second threshold.

4. (Original) The method of claim 3 wherein said apportioning further comprises
polling said local IP address pool at predetermined intervals to obtain local IP
address pool utilization information.
5. (Original) The method of claim 3 wherein
said requesting further comprises requesting a subnet having first predetermined
number of IP addresses; and
said releasing further comprises releasing a subnet having a second predetermined
number of IP addresses.
6. (Original) The method of claim 3 wherein
said requesting further comprises requesting a subnet having a size that is relative to
a current subnet size; and
said releasing further comprises releasing a subnet having a size that is relative to
said current subnet size.
7. (Original) The method of claim 3 wherein
said requesting further comprises requesting a subnet having a size that is relative to
an initial subnet size; and

said releasing further comprises releasing a subnet having a size that is relative to
said initial subnet size.

8. (Currently Amended) The method of claim 3 wherein
said requesting further comprises requesting a subnet having a predetermined size
~~that is relative to a current subnet size~~; and
said releasing further comprises releasing a subnet having a said predetermined size
~~that is relative to said current subnet size~~.
9. (Original) The method of claim 3 wherein said releasing further comprises removing
the summarized route for said one or more subnet from a routing table associated
with said local IP address pool.
10. (Original) The method of claim 8 wherein said method further comprises inserting a
route summary for said requested one or more subnet if said requested one or more
subnet is received.
11. (Original) The method of claim 8 wherein said method further comprises:
inserting a route summary for a received one or more subnet and requesting one or
more subnet if the size of said received one or more subnet is less than the size
of said requested one or more subnet;
inserting a route summary for said received one or more subnet if the size of said
received one or more subnet equals the size of said requested one or more

subnet;

inserting a route summary for said received one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization falls below said second threshold; and

rejecting said received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization does not fall below said second threshold.

12. (Original) The method of claim 1 wherein said remote domain comprises a virtual private network (remote domain).
13. (Original) A program storage device readable by a machine, embodying a program of instructions executable by the machine to perform a method for on-demand management of Internet Protocol (IP) address pools, the method comprising:
allocating an unused IP address from a local IP address pool designated for a remote domain if a request to connect to said remote domain is received, said local IP address pool comprising one or more of at least one subnet obtained from a global IP address pool, each of said at least one subnet specifying a contiguous set of one or more IP addresses;
deallocating an IP address back to said local IP address pool if said IP address is unused; and

apportioning one or more of said at least one subnet between said global IP address pool and said local IP address pool based upon utilization of said local IP address pool.

14. (Original) The program storage device of claim 13, said method further comprising configuring said local IP address pool with a subnet from said at least one subnet.

15. (Original) The program storage device of claim 13 wherein said apportioning comprises:
requesting one or more subnet from said global IP address pool if utilization of said local IP address pool exceeds a first threshold; and
releasing one or more subnet to said global IP address pool if utilization of said local IP address pool falls below a second threshold.

16. (Original) The program storage device of claim 15 wherein said apportioning further comprises polling said local IP address pool at predetermined intervals to obtain local IP address pool utilization information.

17. (Original) The program storage device of claim 15 wherein
said requesting further comprises requesting a subnet having first predetermined number of IP addresses; and
said releasing further comprises releasing a subnet having a second predetermined number of IP addresses.

18. (Original) The program storage device of claim 15 wherein
said requesting further comprises requesting a subnet having a size that is relative to
a current subnet size; and
said releasing further comprises releasing a subnet having a size that is relative to
said current subnet size.
19. (Original) The program storage device of claim 15 wherein
said requesting further comprises requesting a subnet having a size that is relative to
an initial subnet size; and
said releasing further comprises releasing a subnet having a size that is relative to
said initial subnet size.
20. (Currently Amended) The program storage device of claim 15 wherein
said requesting further comprises requesting a subnet having a predetermined size
~~that is relative to a current subnet size~~; and
said releasing further comprises releasing a subnet having a said predetermined size
~~that is relative to said current subnet size~~.
21. (Original) The program storage device of claim 15 wherein said releasing further
comprises removing the summarized route for said one or more subnet from a
routing table associated with said local IP address pool.
22. (Original) The program storage device of claim 20 wherein said method further

comprises inserting a route summary for said requested one or more subnet if said requested one or more subnet is received.

23. (Original) The program storage device of claim 20 wherein said method further comprises:

inserting a route summary for a received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is less than the size of said requested one or more subnet;

inserting a route summary for said received one or more subnet if the size of said received one or more subnet equals the size of said requested one or more subnet;

inserting a route summary for said received one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization falls below said second threshold; and

rejecting said received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization does not fall below said second threshold.

24. (Original) The program storage device of claim 13 wherein said remote domain comprises a virtual private network (remote domain).

25. (Original) An apparatus for on-demand management of Internet Protocol (IP) address pools, the apparatus comprising:
- means for allocating an unused IP address from a local IP address pool designated for a remote domain if a request to connect to said remote domain is received, said local IP address pool comprising one or more of at least one subnet obtained from a global IP address pool, each of said at least one subnet specifying a contiguous set of one or more IP addresses;
- means for deallocating an IP address back to said local IP address pool if said IP address is unused; and
- means for apportioning one or more of said at least one subnet between said global IP address pool and said local IP address pool based upon utilization of said local IP address pool.
26. (Original) The apparatus of claim 25, further comprising means for configuring said local IP address pool with a subnet from said at least one subnet.
27. (Original) The apparatus of claim 25 wherein said means for apportioning comprises:
- means for requesting one or more subnet from said global IP address pool if utilization of said local IP address pool exceeds a first threshold; and
- means for releasing one or more subnet to said global IP address pool if utilization of said local IP address pool falls below a second threshold.

28. (Original) The apparatus of claim 27 wherein said means for apportioning further comprises means for polling said local IP address pool at predetermined intervals to obtain local IP address pool utilization information.
29. (Original) The apparatus of claim 27 wherein
said means for requesting further comprises means for requesting a subnet having
first predetermined number of IP addresses; and
said means for releasing further comprises means for releasing a subnet having a
second predetermined number of IP addresses.
30. (Original) The apparatus of claim 27 wherein
said means for requesting further comprises means for requesting a subnet having a
size that is relative to a current subnet size; and
said means for releasing further comprises means for releasing a subnet having a size
that is relative to said current subnet size.
31. (Original) The apparatus of claim 27 wherein
said means for requesting further comprises means for requesting a subnet having a
size that is relative to an initial subnet size; and
said means for releasing further comprises means for releasing a subnet having a size
that is relative to said initial subnet size.
32. (Currently Amended) The apparatus of claim 27 wherein

said means for requesting further comprises means for requesting a subnet having a predetermined size ~~that is relative to a current subnet size~~; and

said means for releasing further comprises means for releasing a subnet having a said predetermined size ~~that is relative to said current subnet size~~.

33. (Original) The apparatus of claim 27 wherein said means for releasing further comprises means for removing the summarized route for said one or more subnet from a routing table associated with said local IP address pool.
34. (Original) The apparatus of claim 32 wherein said apparatus further comprises means for inserting a route summary for said requested one or more subnet if said requested one or more subnet is received.
35. (Original) The apparatus of claim 32 wherein said apparatus further comprises:
means for inserting a route summary for a received one or more subnet and means
for requesting one or more subnet if the size of said received one or more subnet
is less than the size of said requested one or more subnet;
means for inserting a route summary for said received one or more subnet if the size
of said received one or more subnet equals the size of said requested one or
more subnet;
means for inserting a route summary for said received one or more subnet if the size
of said received one or more subnet is greater than the size of said requested one
or more subnet and if the resulting local IP address pool utilization falls below

said second threshold; and

means for rejecting said received one or more subnet and means for requesting one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization does not fall below said second threshold.

36. (Original) The apparatus of claim 25 wherein said remote domain comprises a virtual private network (remote domain).

37. (Original) An apparatus for on-demand management of Internet Protocol (IP) address pools, the apparatus comprising:

an allocator to allocate an unused IP address from a local IP address pool designated for a remote domain if a request to connect to said remote domain is received, said local IP address pool comprising one or more of at least one subnet obtained from a global IP address pool, each of said at least one subnet specifying a contiguous set of one or more IP addresses, said allocator coupled to said local IP address pool;

a deallocator to deallocate an IP address back to said local IP address pool if said IP address is unused, said deallocator coupled to said local IP address pool; and

a monitor to apportion one or more of said at least one subnet between said global IP address pool and said local IP address pool based upon utilization of said local IP address pool, said monitor coupled to said local IP address pool and a global IP address pool interface.

38. (Original) The apparatus of claim 37, further comprising an IP address configurer to configure said local IP address pool with a subnet from said at least one subnet.
39. (Original) The apparatus of claim 37 wherein said monitor comprises:
- a utilization assessor to assess utilization of said local IP address pool, said utilization assessor coupled to said local IP address pool;
 - a subnet requestor to request a subnet from said global IP address pool if utilization of said local IP address pool exceeds a first threshold;
 - a subnet receiver to receive said requested subnet and to forward said requested subnet to said local IP address pool, said subnet receiver coupled to said local IP address pool and said global IP address pool interface; and
 - a subnet returner to return a subnet to said local IP address pool if said utilization assessor indicates utilization of said local IP address pool is below a second threshold, said subnet returner coupled to said local IP address pool and said global IP address pool interface.
40. (Original) The apparatus of claim 39 wherein said utilization assessor is further configured to poll said local IP address pool at predetermined intervals to obtain local IP address pool utilization information.
41. (Original) The apparatus of claim 39 wherein said subnet requestor is further configured to request a subnet having first predetermined number of IP addresses; and

said subnet returner is further configured to release a subnet having a second
predetermined number of IP addresses.

42. (Original) The apparatus of claim 39 wherein

said subnet requestor is further configured to request a subnet having a size that is
relative to a current subnet size; and
said subnet returner is further configured to release a subnet having a size that is
relative to said current subnet size.

43. (Original) The apparatus of claim 39 wherein

said subnet requestor is further configured to request a subnet having a size that is
relative to an initial subnet size; and
said subnet returner is further configured to release a subnet having a size that is
relative to said initial subnet size.

44. (Currently Amended) The apparatus of claim 39 wherein

said subnet requestor is further configured to request a subnet having a
predetermined size ~~that is relative to a current subnet size~~; and
said subnet returner is further configured to release a subnet having a said
predetermined size ~~that is relative to said current subnet size~~.

45. (Original) The apparatus of claim 39 wherein said subnet returner is further
configured to remove the summarized route for said one or more subnet from a

routing table associated with said local IP address pool.

46. (Original) The apparatus of claim 44 wherein said subnet receiver is further configured to insert a route summary for said requested one or more subnet if said requested one or more subnet is received.
47. (Original) The apparatus of claim 44 wherein said subnet receiver is further configured to:
- insert a route summary for a received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is less than the size of said requested one or more subnet;
 - insert a route summary for said received one or more subnet if the size of said received one or more subnet equals the size of said requested one or more subnet;
 - insert a route summary for said received one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization falls below said second threshold; and
 - reject said received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization does not fall below said second threshold.

48. (Original) The apparatus of claim 37 wherein said remote domain comprises a virtual private network (remote domain).
49. (Original) The apparatus of claim 37 wherein
said global IP address pool comprises an Authentication, Authorization and
Accounting (AAA) server; and
said global IP address interface comprises an AAA proxy configured to
communicate with said AAA server using the RADIUS protocol.
50. (Original) The apparatus of claim 37 wherein
said global IP address pool comprises a Dynamic Host Configuration Protocol
(DHCP) server; and
said global IP address interface comprises a Ring Access Controller (RAC) client
configured to communicate with said DHCP server using the DHCP protocol.
51. (New) A method for on-demand management of Internet Protocol (IP) address
pools, the method comprising:
allocating an unused IP address from a local IP address pool designated for a remote
domain if a request to connect to said remote domain is received, said local IP
address pool comprising one or more of at least one subnet obtained from a
global IP address pool, each of said at least one subnet specifying a contiguous
set of one or more IP addresses;
deallocating an IP address back to said local IP address pool if said IP address is

unused;

apportioning one or more of said at least one subnet between said global IP address pool and said local IP address pool based upon utilization of said local IP address pool, said apportioning further comprising:

requesting one or more subnet from said global IP address pool if utilization of said local IP address pool exceeds a first threshold, said one or more subnet having a size that is relative to a current subnet size; and

releasing one or more subnet to said global IP address pool if utilization of said local IP address pool falls below a second threshold, said one or more subnet having a size that is relative to said current subnet size;

inserting a route summary for a received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is less than the size of said requested one or more subnet;

inserting a route summary for said received one or more subnet if the size of said received one or more subnet equals the size of said requested one or more subnet;

inserting a route summary for said received one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization falls below said second threshold; and

rejecting said received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization does not

fall below said second threshold.

52. (New) A program storage device readable by a machine, embodying a program of instructions executable by the machine to perform a method for on-demand management of Internet Protocol (IP) address pools, the method comprising:
- allocating an unused IP address from a local IP address pool designated for a remote domain if a request to connect to said remote domain is received, said local IP address pool comprising one or more of at least one subnet obtained from a global IP address pool, each of said at least one subnet specifying a contiguous set of one or more IP addresses;
- deallocating an IP address back to said local IP address pool if said IP address is unused;
- apportioning one or more of said at least one subnet between said global IP address pool and said local IP address pool based upon utilization of said local IP address pool, said apportioning further comprising:
- requesting one or more subnet from said global IP address pool if utilization of said local IP address pool exceeds a first threshold, said one or more subnet having a size that is relative to a current subnet size; and
- releasing one or more subnet to said global IP address pool if utilization of said local IP address pool falls below a second threshold, said one or more subnet having a size that is relative to said current subnet size;
- inserting a route summary for a received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is less than the size

of said requested one or more subnet;
inserting a route summary for said received one or more subnet if the size of said
received one or more subnet equals the size of said requested one or more
subnet;
inserting a route summary for said received one or more subnet if the size of said
received one or more subnet is greater than the size of said requested one or
more subnet and if the resulting local IP address pool utilization falls below said
second threshold; and
rejecting said received one or more subnet and requesting one or more subnet if the
size of said received one or more subnet is greater than the size of said requested
one or more subnet and if the resulting local IP address pool utilization does not
fall below said second threshold.

53. (New) An apparatus for on-demand management of Internet Protocol (IP) address
pools, the apparatus comprising:

means for allocating an unused IP address from a local IP address pool designated
for a remote domain if a request to connect to said remote domain is received,
said local IP address pool comprising one or more of at least one subnet
obtained from a global IP address pool, each of said at least one subnet
specifying a contiguous set of one or more IP addresses;

means for deallocating an IP address back to said local IP address pool if said IP
address is unused;

means for apportioning one or more of said at least one subnet between said global

IP address pool and said local IP address pool based upon utilization of said local IP address pool, said means for apportioning further comprising:

means for requesting one or more subnet from said global IP address pool if utilization of said local IP address pool exceeds a first threshold, said one or more subnet having a size that is relative to a current subnet size; and

means for releasing one or more subnet to said global IP address pool if utilization of said local IP address pool falls below a second threshold, said one or more subnet having a size that is relative to said current subnet size;

means for inserting a route summary for a received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is less than the size of said requested one or more subnet;

means for inserting a route summary for said received one or more subnet if the size of said received one or more subnet equals the size of said requested one or more subnet;

means for inserting a route summary for said received one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization falls below said second threshold; and

means for rejecting said received one or more subnet and requesting one or more subnet if the size of said received one or more subnet is greater than the size of said requested one or more subnet and if the resulting local IP address pool utilization does not fall below said second threshold.

54. (New) An apparatus for on-demand management of Internet Protocol (IP) address pools, the apparatus comprising:
- an allocator to allocate an unused IP address from a local IP address pool designated for a remote domain if a request to connect to said remote domain is received, said local IP address pool comprising one or more of at least one subnet obtained from a global IP address pool, each of said at least one subnet specifying a contiguous set of one or more IP addresses, said allocator coupled to said local IP address pool;
 - a deallocator to deallocate an IP address back to said local IP address pool if said IP address is unused, said deallocator coupled to said local IP address pool;
 - a monitor to apportion one or more of said at least one subnet between said global IP address pool and said local IP address pool based upon utilization of said local IP address pool, said monitor coupled to said local IP address pool and a global IP address pool interface, said monitor comprising:
 - a utilization assessor to assess utilization of said local IP address pool, said utilization assessor coupled to said local IP address pool;
 - a subnet requestor to request a subnet from said global IP address pool if utilization of said local IP address pool exceeds a first threshold, said subnet having a size that is relative to a current subnet size;
 - a subnet receiver to receive said requested subnet and to forward said requested subnet to said local IP address pool, said subnet receiver coupled to said local IP address pool and said global IP address pool interface, said subnet having a size that is relative to said current subnet size, said subnet receiver

configured to:

insert a route summary for a received one or more subnet and requesting

one or more subnet if the size of said received one or more subnet is

less than the size of said requested one or more subnet;

insert a route summary for said received one or more subnet if the size of

said received one or more subnet equals the size of said requested one

or more subnet;

insert a route summary for said received one or more subnet if the size of

said received one or more subnet is greater than the size of said

requested one or more subnet and if the resulting local IP address pool

utilization falls below said second threshold; and

reject said received one or more subnet and requesting one or more subnet if

the size of said received one or more subnet is greater than the size of

said requested one or more subnet and if the resulting local IP address

pool utilization does not fall below said second threshold; and

a subnet returner to return a subnet to said local IP address pool if said

utilization assessor indicates utilization of said local IP address pool is

below a second threshold, said subnet returner coupled to said local IP

address pool and said global IP address pool interface.